

PATENT APPLICATION COVER SHEET  
Attorney Docket No. 0212.66402

*I hereby certify that this paper is being deposited with the United States Postal Service as Express Mail in an envelope addressed to: Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on this date.*

1/14/2004  
Date

  
Express Mail No.: EV 032697968 US

Inventors: Wolfgang Hirschburger, Markus Allemann & Illya Kovarik.

NOSE TIP CONTROL FOR CORDLESS HIGH SPEED ROTARY TOOL

GREER, BURNS & CRAIN, LTD.  
300 South Wacker Drive, Suite 2500  
Chicago, Illinois 60606  
Telephone: (312) 360-0080  
CUSTOMER NO. 24978

## NOSE TIP CONTROL FOR CORDLESS HIGH SPEED ROTARY TOOL

### 1 Field of the Invention

2 The instant invention is related to control mechanisms for rotary  
3 hand tools.

### 4 Background of the Invention

5 The present invention generally relates to a control mechanism for  
6 an electrical powered rotary hand tool that more particularly includes an actuator  
7 having a configuration and location that reduces or eliminates an operator's need  
8 to alter a grip on the rotary hand tool when controlling the actuation of the rotary  
9 hand tool.

10 Electrical slide switches have long been used to control the operation  
11 of many electrical powered rotary hand tools, principally for actuating, deactuating  
12 and controlling the operating speed of many kinds of variable speed hand tools.  
13 One exemplary hand tool with which these electrical slide switches have  
14 conventionally been used are those used in woodworking and the like as marketed  
15 by the Robert Bosch Power Tool Company of Chicago, IL under the Dremel  
16 trademark. Such tools have an elongated generally cylindrical configuration with  
17 a rotating output shaft at the nose end to which various tools can be attached for  
18 performing tasks such as engraving, carving, polishing, cleaning, cutting, grinding,  
19 sharpening and sanding. Many of these tools have a variable speed capability  
20 which is controlled by operation of a slide switch that is located near the rear end  
21 of the tool and which is movable in a circumferential direction between an off  
22 position and a maximum speed position.

Light touch switches have conventionally been provided in devices wherein depression of the switch had a first desired effect and release of the switch had a second desired effect, such as in handheld calculators. Light touch switches are advantageous in that they are relatively small, may be configured to be generally flat or flush with a surface of the device, and are relatively simple to operate.

## 7 Summary of the Invention

8           The preferred embodiment of present invention is an improved  
9 control mechanism for an electrical powered rotary hand tool that includes a  
10 preferably light touch switch of the type having at least two positions or states,  
11 wherein a first position or state activates the hand tool and a second position or  
12 state for deactivates the hand tool. The control mechanism is preferably sized and  
13 configured so that a predetermined small amount of pressure actuates the  
14 mechanism, thereby either activating or deactivating the hand tool. The control  
15 mechanism is also preferably disposed at a predetermined location on the hand  
16 tool so that an operator may activate or deactivate the hand tool with reduced or  
17 eliminated hand movement.

## 18 Description of the Drawings

FIGURE 1 is a top plan view of one embodiment of an exemplary tool with which a preferred embodiment of the control mechanism of the instant invention may be operated;

FIG. 2 is a perspective view of another embodiment of an exemplary tool;

FIG. 3 is an exploded view of the exemplary tool illustrated in FIG. 1;

26 FIG. 4 is a side perspective view of a light touch switch; and

1                   FIG. 5 is a schematic circuit diagram illustrating circuitry that may  
2   be used in the preferred embodiment shown in FIG. 1.

### 3                   Detailed Description of the Preferred Embodiments

4                   Broadly stated, the present invention is directed to a control  
5   mechanism for an electrical powered rotary hand tool that includes a light touch  
6   switch of the type that controls an electronic control circuit that controls the hand  
7   tool motor. The light touch switch includes at least two positions, a first position  
8   that enables the electronic control circuit, thereby activating the rotary hand tool,  
9   and a second position that disables the electronic control circuit, thereby  
10   deactivating the rotary hand tool. It should be understood that the control circuit  
11   controls the operation of the motor and therefore switches the motor current during  
12   operation, the light touch switch controls the control circuit and does not have to  
13   switch the motor current and can therefore be a much smaller switch.

14                  While the control mechanism of the instant invention is  
15   contemplated for use in any electronic device wherein an operator manually  
16   controls both activation and deactivation of the device, for purposes of illustration,  
17   the instant invention will be shown and described with an electrical powered  
18   rotary hand tool of the type having an elongated, generally cylindrical  
19   configuration with a rotating output shaft at a nose end to which various tools can  
20   be attached for performing tasks such as engraving, carving, polishing, cleaning,  
21   cutting, grinding, sharpening and sanding.

22                  Turning now to FIG. 1, the exemplary electrical powered rotary hand  
23   tool operated by a preferred embodiment of the control mechanism of the instant  
24   invention is illustrated generally at 10. The electrical powered rotary hand tool 10,  
25   includes a generally cylindrical housing that includes a nose end portion 12 from  
26   which an output shaft 14 extends, and a center motor portion 16, which houses the  
27   motor (not shown) that drives the output shaft 14. A battery pack 18 is optionally  
28   included at the rear end of the housing, but may not be present in tools powered

1 via a power cord. A depressible locking lever 19 is also preferably provided  
2 which is configured to engage an opening in the output shaft 14 to prevent rotation  
3 thereof while a bit or other tool is being attached to the tool 10.

4 Intermediate of the nose portion 12 and the motor portion 16 is an  
5 electrical slide switch 20 that is coupled to the control circuit to control the  
6 variable rotating speed of the motor. The electrical slide switch 20 preferably  
7 provides a variable electrical resistance value, which can be used in circuit to vary  
8 operating parameters as a function of the position of a switch lever.

9 During operation, an operator typically grips the tool 10 around the  
10 nose portion 12, similar to the manner in which an operator would grip a pen or  
11 pencil. Ergonomically, it is preferable that the nose portion taper in circumference  
12 at the nose end near the output shaft 14, so that an operator may comfortably grip  
13 the nose portion and maintain optimum control over the tool 10. While the  
14 tapered nose portion 12 is ergonomically advantageous, it does reduce the surface  
15 area available for accessories. For example, size considerations alone suggest that  
16 the slide switch 20 presently illustrated would likely require modification if it were  
17 to be disposed on the tapered nose portion 12. However, the surface area of the  
18 tapered nose portion 12 is sufficiently large that a small switch may be configured  
19 to be disposed thereon.

20 Accordingly, as illustrated in FIG. 3, the preferred embodiment of  
21 the instant invention contemplates an improved control system for the tool 10 that  
22 includes a light touch switch 30 disposed on a portion of the nose portion 12. In  
23 this embodiment, the light touch switch 30 is disposed such that during the  
24 ordinary course of operation, the operator may actuate the light touch switch  
25 without any significant regripping of the tool 10. As is best seen in the  
26 embodiment illustrated in FIG. 2, the operator may conveniently grip the nose  
27 portion 12 of the tool 12 much like one would grip a pencil, with the nose portion  
28 being gripped between the thumb and the first two fingers and with the center  
29 portion 16 resting in the base of the thumb and first finger. In this position, the

1 first finger is located very close to the switch 30 so that it may be actuated without  
2 any substantial regripping of the tool.

3 Turning now to FIG. 4, the light touch switch 30 preferably includes  
4 a generally rectangular housing 32 having a predetermined depth and a generally  
5 planar top surface, through which a generally rectangular movable switch element  
6 34 extends. The switch element 34 is preferably spring-biased within the housing  
7 32 in an extended position. Compression of the spring allows depression of the  
8 switch element and a corresponding actuation of the switch 30. Preferably, a top  
9 surface of the switch element 34 is generally coextensive with a surface of the tool  
10 10.

11 Electrical contact legs 36 extend from a bottom surface of the  
12 housing 32. The tapered nose portion 12 of the tool has a limited surface area and  
13 volume to accommodate electrical components. Therefore, the size of the light  
14 touch switch 30 is preferably minimized to consume the least amount of surface  
15 area and depth, while being large enough to impart tactile qualities to the switch to  
16 enhance ease of operation of the switch. In the preferred embodiment, the housing  
17 32 has a length of approximately 6.0 mm, a width of approximately 3.5 mm, and a  
18 depth of approximately 3.5 mm, exclusive of the depth added by the contacts 36.  
19 The switch element 34 preferably has a length of approximately 3.0 mm, and a  
20 width of approximately 1.4 mm.

21 The nose portion 12 of the tool accordingly includes a  
22 correspondingly sized and configured recess for receiving the light touch switch  
23 30. The recess is configured so that the light touch switch 30 fits within the  
24 recess, in a manner whereby the top surface of the switch element 34 is generally  
25 coextensive with the top surface of the nose portion 12.

26 Preferably, the light touch switch 30 includes at least two positions  
27 or states: a first open circuit position or state in which the tool 10 is deactivated,  
28 and a second closed circuit position or state, wherein the tool is activated. In the  
29 preferred embodiment, the light touch switch 30 is provided in addition to the slide

1 switch 20, which controls the operating speed. The light touch switch 30  
2 selectively enables and disables an electrical control circuit that controls the  
3 operation of the tool motor. Because the light touch switch 30 does not directly  
4 switch the motor, it does not have to conduct or switch the motor load current and  
5 is therefore much more susceptible to miniaturization. When enabled, motor  
6 current reaches the output shaft, and when disabled, the motor current is prevented  
7 from reaching the output shaft, thereby resulting in either actuation or  
8 deactivation.

9           As illustrated in FIG. 5, an electrical control and drive circuit for the  
10 tool is illustrated together with a light touch switch 34. The tool motor 40 is  
11 connected to a power source 42 that can be AC or DC. The motor speed of  
12 operation is controlled by an oscillator 44 that is controlled by the speed setting  
13 slide switch 20, with the oscillator providing a pulsed output on line 46 that  
14 extends to a switching transistor 48 that switches the current that flows through the  
15 motor. The duty cycle of the pulsed output is a function of the position of the slide  
16 switch 20 and thereby varies the operating speed accordingly. The power source  
17 42 also extends through line 50, the light touch switch 34 and line 52 to power the  
18 oscillator 44. When the switch 34 is closed, the oscillator 44 will operate and  
19 when the switch is opened, the oscillator will be disabled. Since the amount of  
20 power necessary to operate the oscillator is relatively small, the small switch 34  
21 can effectively provide an on/off switching capability of the motor 40. Thus, the  
22 light touch switch 30 of the instant invention is preferably one of a variety of  
23 switches denominated as "light touch switches," wherein a predetermined amount  
24 of pressure will depress the switch element 34, resulting in actuation of the tool  
25 10. In the preferred embodiment of the instant invention, actuation of the tool 10  
26 may be accomplished by depressing the light touch switch to a depth of only  
27 approximately 1/16 of an inch. When disposed on or within the tapered nose  
28 portion 12, the light touch switch 30 preferably includes a tactile surface that  
29 engages either the operator's finger or an intermediate material, and it may be

1 perceived by the operator to the touch, either directly or through an intermediate  
2 material.

3           The preferred embodiment of the instant invention further includes a  
4 thin layer of flexible material, or grip layer 38, that is intermediate the light touch  
5 switch 30 and the operator's finger. The grip layer 38, when present, serves a  
6 variety of purposes. First, the grip layer 38 is preferably composed of a rubber  
7 material such as TPE, and thereby promotes the overall grip on the tool 10 by the  
8 operator. The rubber of the grip layer 38 is preferably textured, and may  
9 additionally be grooved to enhance gripping properties, and creates additional  
10 friction between the surface of the grip layer and the portions of the operator's  
11 hands in contact with the surface. Second, in addition to the tactile properties of  
12 rubber, the rubber provides a cushioned grip for the operator.

13           The grip layer 38 of the preferred embodiment is disposed over the  
14 portion of the nose portion 12 housing the light touch switch 30 and that portion of  
15 the nose portion wherein the operator's hand typically grips the tool 10. Thus, the  
16 grip layer 38 of the preferred embodiment includes a predetermined structure, but  
17 that structure may be varied to suit individual applications or even individual  
18 operators. For example, turning now to FIGS. 1 and 3, a majority of the nose  
19 portion 12 is covered by the grip layer 38, ensuring that a multitude of hand  
20 positions by the operator will confer the advantages of the grip layer.

21           The grip layer 38 may be configured to include additional preferable  
22 features as well. For example, the grip layer 38 may include one or more textured  
23 portions 54 that may include ribs 56 or recesses or other patterns. The textured  
24 portions 54 may themselves be recessed so that a radius measured from a  
25 longitudinal axis of the tool 10 to the textured portions is less than that as  
26 measured from the longitudinal axis to the balance of the nose portion 12. This  
27 configuration enhances operator grip as well.

28           With respect to the light touch switch 30, the grip portion 38 may be  
29 further configured to enhance actuation of the tool 10. Preferably, the grip portion



1 38 may optionally include indicia to demarcate the location of the light touch  
2 switch 30, such as a small, generally circular opening 58 that reveals a clearly  
3 colored portion of the light touch switch. However, even in the absence of visual  
4 indicia, the constituent material of the grip layer 38 is such that the operator may  
5 perceive the switch via touch underneath the grip layer as a protruberance  
6 underneath the grip layer. Thus, compression of the grip layer 38 may cause  
7 compression of the light touch switch 30 when an underside of the grip layer abuts  
8 and compresses the light touch switch into the second position. As illustrated in  
9 the embodiment represented by FIG. 2, even in the absence of visual indicia, the  
10 operator may compress the area of the grip layer 38 that generally corresponds to a  
11 location of the underlying light touch switch 30 to actuate the switch.

12 As further indication of the location and position of the light touch  
13 switch 30, the light touch switch may preferably be configured to include a  
14 positive feedback mechanism, such as an audible indication of depression into the  
15 second position or state and subsequent release into the first position or state. The  
16 audible indication may be as simple as a click that sounds as the switch element 34  
17 is depressed. In addition to being audible, such a click may also be perceived by  
18 the operator via touch.

19 The preferred embodiment of the present invention includes a light  
20 touch switch 30 having a detented or clicking action so that the operator can easily  
21 perceive movement that is being made by the light touch switch during operation  
22 and also hold the switch in its desired location. The preferred detenting action  
23 provides sufficient level of resistance to initial movement that the likelihood that  
24 the light touch switch 30 will move without a conscious force being applied to it is  
25 quite small. If the light touch switch 30 is being used in a rotating hand tool such  
26 as a Dremel tool, normal vibration experienced during operation of the tool should  
27 not affect the position of the switch 30. Also, the resistance to movement  
28 provided by the detenting action of the switch mechanism will not result in

1 movement of the switch 30 by most levels of incidental contact that is experienced  
2 during use.

3           While various embodiments of the present invention have been  
4 shown and described, it should be understood that other modifications,  
5 substitutions and alternatives are apparent to one of ordinary skill in the art. Such  
6 modifications, substitutions and alternatives can be made without departing from  
7 the spirit and scope of the invention, which should be determined from the  
8 appended claims.

9           Various features of the invention are set forth in the following  
10 claims.